## Professional Dishwashers

The **PG 8055 SPEED** and **PG 8056 SPEEDPlus** are the fastest commercial dishwashers using the fresh water circulation system and are ideal for hotels, restaurants, clubs and schools. With its shortest wash cycle of just 5 minutes it can wash up to 456 plates an hour. Two rack levels add to it's flexibility and cleaning performance.

The **PG 8058 BRILLIANT** produces perfect wash results with a sparkling finish, dispensing with the need to polish glassware and cutlery if supplied from a Reverse Osmosis (RO) water system. This feature combined with the fresh water circulation system are unique to Miele Professional. The PG 8058 BRILLIANT model is recommended by Riedel for their on-premise glasses.

The **PG 8059 HYGIENE** dishwashers with its uncompromising cleaning system provides exceptionally high standards of hygiene making it ideal for hospitals, nursing homes and nursery schools.

	PG 8055	PG 8056	PG 8058	PG 8059
	SPEED	SPEEDplus	BRILLIANT	HYGIENE
Design				
Freshwater System	х	х	x	x
Freestanding	x	X 1	x	x
Door Lock	Easy Open	Easy Open	Auto Open	Auto Open
Controls				
TouchControl	х	х	x	x
Number of programmes	12	13	14	13
Shortest programme cycle (mins)	9	6 at 55°C	6 at 55°C	6 at 55°C 15 at 85°C
Capacity				
Plate capacity (plates/h)	225	456	456	456
Programmes Cycle duration* / final rinse °C				
Super short 6/55		X	X	X
Short 9/60	X	X	X	
Short (with thermal disinfection) 15/85				X
Universal 12/60	X	X	X	
Universal (with thermal disinfection) 25/85				X
Intensive 16/60	Х	X	X	
Intensive (with thermal disinfection) -/85				X
Glasses 9/50	Х	X	X	X
Glasses special -/50			X	

<sup>\*</sup>when connected to AC 230V 50Hz (30-32Amps) and hot water (65°C) 1- Or built under (PG 8056U) x Standard feature - Feature not available

## Products Professional Dishwashers

	PG 8055	PG 8056	PG 8058	PG 8059
	SPEED	<b>SPEED</b> plus	BRILLIANT	HYGIENE
Programmes contd	••••	••••	•••	••••
Programmes Cycle duration* / final rinse °C				
Beer Glasses -/cold	X	X	X	X
Hygiene -/70	X	X		
Hygiene Plus -/83			X	X
Cutlery -/55	X	X	X	X
Plastics 15/60	X	X	X	X
EnergySave 23/50	X	X	X	X
Reactivation -/-	X	X	X	X
Cold 3.5/-	X	X	X	X
Drainage -/-	X	X	X	X
Dispenser systems				
Salt dispenser in door	X	X	Χ	X
1 x combi door dispenser for powder detergent and surfactant	Х	X	X	Х
Water softener Hot and cold water, max 65°C, water hardness 60° dH	x	×	X	×
Water Connection				
Cold or hot water connection, max. 65°C	X	-	-	-
Cold water connection, max. 20°C	-	X	X	X
Hot water connection, max. 65°C	-	X	X	X
Demineralised water connection	-	-	X	-
Electrical connection				
3N AC 400 V, 50 Hz, with 1.7m cable & plug	-	X	-	X
1N AC 230 V, 50 Hz	Χ	X	X	X
Heating (kW)	5.5	5.5/8.5	5.5	5.5/8.5
Heater pump (kW)	0.4	0.4	0.4	0.4
Total rated load (kW)	5.9	5.9/8.9	5.9	5.9/8.9
Fuse rating (kW)	3x16	3x16	3x16	3x16
Dimensions, weight				
External dimensions H/W/D [mm]	835/598/580	835/598/580	835/598/598	835/598/598
Net weight [kg]	70	70	70	70
External finish	White	White or Stainless Steel	Stainless Steel	White or Stainless Steel
Sound levels (db (A) re 1 pW)				
Sound emissions	59	59	59	57

<sup>\*</sup>when connected to AC 230V 50Hz (30-32Amps) and hot water (65°C)  ${\bf x}$  Standard feature  ${\bf o}$  Optional feature  ${\bf o}$  - Feature not available





